




# TC-610


### **Professional Water Resistant**

## **Two-Way Radio**

The TC-610 is ideal for construction, industrial, & other applications looking for affordable yet reliable communications in a compact & durable design. Its IP66-rated water protection make it extremely useful for jobs that may encounter wet environments during the work day or may need to wash the radio after use in a dirty environment. The TC-610 has a 2000mAh Li-Ion battery & the choice of either a yellow/black or all-black colors.









**Powerful Audio and Wide Communication Range** 

High-Capacity 2000mAh Li-Ion Battery

All-Black Version Available for Discrete Applications

**Easy-Grip Design Prevents Drops** 



# Professional Two-way Radio

# **Technical Highlights**

- IP66-Rated Water & Dust Protection Protects against water intrusion from stream of water measuring 1.6 inches.
- Unique Easy-Grip Design The unique easy-grip design provides increased security against dropping.
- High-Capacity 2000 mAh Li-lon Battery TC-610 has long battery life (over 14 hours) with a high capacity battery.
- All-Black Version Available for Discrete Applications The TC-610 also comes in All-Black color for when the application requires discretion such as for Casinos, Funeral Escorts, Security, and Hotels.
- Patented Battery Latch The unique battery latch design prevents separation from battery when dropped.
- Voice Operated Transmit (VOX) Hands-free transmit is possible, when paired with an applicable accessory.

#### Main Features

- High / Low Power Switchable
- Battery Save & Low Battery Alert
- Programmable Channel Spacing (Wide / Narrow Band Selectable)
- LED Battery Gauge
- Time-Out Timer
- TX Admit
- CTCSS / CDCSS Encode & Decode
- Data Operated Squelch
- Selectable Squelch Level (0-9)
- Channel Scan
- PC Programmable
- Wired Clone
- ATIS

#### General ———

Frequency Range (MHz)	VHF: 136-174 UHF: 400-420*; 450-470
Channel Capacity	16
Channel Spacing (kHz)	25 kHz / 12.5 kHz
PLL Channel Stepping (kHz)	5 kHz, 6.25 kHz
Operating Voltage (v)	7.4 V
RF Power Output (w)	5W/2W (VHF) 4W/2W (UHF)
Battery	2000 mAh (Li-Ion)
Battery Life (5-5-90 duty cycle)	Over 14 Hours
Frequency Stability (ppm)	± 2.5
Operating Temperature (F°)	-4° ~ +122° (F°)
Antenna Impedance (Ù)	50
Dimensions	4.68 in. x 2.16 in. x 1.30 in.
Weight (with antenna & battery)	9.70 oz.

\*Frequencies Marked with an Asterisk(\*) are for Export Only.

This is not a submersible radio. Full immersion in water is not covered by warranty. All specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development. More detailed specs available upon request.

#### **Recommended Applications -**

- Construction
- Manufacturing

- Warehousing & Industrial









#### Accessories

Standard Accessories

Li-Ion Battery (2000mAh) BL2001 Power Supply PS1037(UL)

MCU Charger CH10A03

Belt Clip BC12

#### Featured Optional Accessories Note: The TC-610 us



















