


WIN91 PT

Thermal Receipt Printer

WINTEC



Printing	WIN91
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line(adjustable by command)
Printing speed	260 mm/s
Interface	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)



Cutter	
Auto cutter	Partial

Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	/// QR CODE / PDF417
Input buffer	64 Kbytes 2048 Kbytes
NV Flash	256 Kbytes 256 Kbytes

Power	
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer	DC 24V/1A

Physical characteristics	
Weight	1.65 Kg
Dimensions	188×145×148mm (D×W×H)

Environmental Requirements	
Operation environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)

Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM

Software	
Emulation	ESC/POS
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows

WINTEC WIN91 PT

